

System Contents:

- Detached WalkAbout III®** - 5.6" LCD Display
- LLC-1.4** - Two (2) Low Light Color Camera
- AP-F3** - 3' Fixed Length Articulating Pole
- AP-T9** - 9' Telescoping/Articulating Pole
- AAM-TB** - Talkback Audio Module & Headphones
- D-BAT** - Two (2) D-Cell Battery Pack
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- A-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

- Dual Mode Thermal Camera**
View human activity with no illumination through smoke, tear gas and dust with thermal imaging.
- Videoscope**
Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).
- Ultra Low Light Camera**
Infrared illumination, highly sensitive low-light BW camera.
- Baton**
2ft. fixed length pole for access in confined spaces.
- Rescue Reel**
Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

SYSTEM PART NUMBERS:

WS-TFRST¹

DISPLAYS

WS=Detached WalkAbout
 WA=Standard WalkAbout

AUDIO

T=AAM-TB (talkback)
 Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



A-CASE



AP-T9



AP-F3



DETACHED WALKABOUT



(2) LLC-1.4



(2) BAT-2



AAM-TB



WBC



WUH



(2) D-BAT

ALTERNATE DISPLAY CONFIGURATIONS



STANDARD WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera & Audio

Model	LLC-1.4 Camera	AAM-TB Talkback Module
Construction	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode

Case

Model	A-CASE
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size	53" x 17" x 6" (135 x 43 x 15cm)
Weight loaded	42 lbs. (19kg)

Poles

Model	AP-T9	AP-F3
Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Single section fixed length fiberglass pole with foam grip
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	
Collapsed / Extended Length	4ft. 3in. / 8ft. 7in. (1.3M / 2.6M)	3 ft. (.9M)
Weight	6.4 lbs. (2.9kg)	3.6 lbs. (1.6kg)

System Contents:

- WM-5.6 WalkAbout III®** - 5.6" LCD Display
- LLC-1.4** - Low-Light Color Camera
- AP-T6** - 6' Telescoping/Articulating Pole
- AAM-TB** - Talkback Audio Module & Headphones
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- B-CASE-BLK** - Nylon Backpack Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Ultra Low Light Camera

Infrared illumination, highly sensitive low-light BW camera.

Baton

2ft. fixed length pole for access in confined spaces.

Rescue Reel

Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

SYSTEM PART NUMBERS:

WS-RS-A6T¹

DISPLAYS

WS=Detached WalkAbout
 WA=Standard WalkAbout

POLES

A6=6' Articulating Pole

AUDIO

T=AAM-TB (talkback)
 Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



B-CASE-BLK



AP-T6



WUH



DETACHED WALKABOUT



LLC-1.4



(2) BAT-2



WBC



AAM-TB

ALTERNATE DISPLAY CONFIGURATIONS



STANDARD WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera & Audio

Model	LLC-1.4 Camera	AAM-TB Talkback Module
Construction	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode

Case

Model	B-CASE-BLK
Construction	Soft, padded black "backpack" style case with shoulder straps. Contains zippered compartments with foam inserts for all components. (Camouflage available)
Size	34" x 14" x 4" (86 x 36 x 10cm) Fits in N-CASE (not included)
Weight loaded	12 lbs. (5.4kg)

Poles

Model	AP-T6
Construction	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.
Collapsed / Extended Length	2 ft. 8 in. / 6 ft. 3 in. (1.9M x .8M)
Weight	5.2 lbs. (2.4kg)

System Contents:

- Detached WalkAbout III®** - 5.6" LCD Display
 - LLC-1.4** - Low Light Color Camera
 - AP-T9** - 9' Telescoping/Articulating Pole
 - AAM-TB** - Talkback Audio Module & Headphones
 - D-BAT** - D-Cell Battery Pack
 - BAT-2** - Two (2) NiMH Rechargeable Batteries
 - WBC** - Battery Charger (Power Supply not shown)
 - A-CASE** - Custom Carrying Case
 - WUH** - Universal Chest Harness
 - SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Ultra Low Light Camera

Infrared illumination, highly sensitive low-light BW camera.

Baton

2ft. fixed length pole for access in confined spaces.

Rescue Reel

Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

SYSTEM PART NUMBERS:

WS-RS-A9T¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

POLES

A9=9' Articulating Pole
A14=14' Articulating Pole

AUDIO

T=AAM-TB (talkback)
Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



A-CASE



AP-T9



DETACHED WALKABOUT



LLC-1.4



AAM-TB



WUH



(2) BAT-2



WBC



D-BAT

ALTERNATE DISPLAY CONFIGURATIONS



STANDARD WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera & Audio			Case	
Model	LLC-1.4 Camera	AAM-TB Talkback Module	Model	A-CASE
Construction	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)		
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode	Size	53" x 17" x 6" (135 x 43 x 15cm)
			Weight loaded	37 lbs. (16.8kg)

Poles	
Model	AP-T9
Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.
Collapsed / Extended Length	4ft. 3in. / 8ft. 7in. (1.3M / 2.6M)
Weight	6.4 lbs. (2.9kg)

System Contents:

- Detached WalkAbout III®** - 5.6" LCD Display
 - WPC-2.5Z** - Color Zoom Camera
 - LLC-1.4** - Low Light Color Camera
 - AP-T9** - 9' Telescoping/Articulating Pole
 - AAM-TB** - Talkback Audio Module & Headphones
 - D-BAT** - D-Cell Battery Pack
 - BAT-2** - Two (2) NiMH Rechargeable Batteries
 - WBC** - Battery Charger (Power Supply not shown)
 - A-CASE** - Custom Carrying Case
 - WUH** - Universal Chest Harness
 - SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

- Dual Mode Thermal Camera**
View human activity with no illumination through smoke, tear gas and dust with thermal imaging.
- Videoscope**
Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).
- Ultra Low Light Camera**
Infrared illumination, highly sensitive low-light BW camera.
- Baton**
2ft. fixed length pole for access in confined spaces.
- Rescue Reel**
Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

SYSTEM PART NUMBERS:

WS-RS-A9TZ¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

POLES

A9=9' Articulating Pole
A14=14' Articulating Pole

AUDIO

T=AAM-TB (talkback)
Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



A-CASE



AP-T9



DETACHED WALKABOUT

WPC-2.5Z

AAM-TB

WUH

LLC-1.4

(2) BAT-2

WBC

D-BAT

ALTERNATE DISPLAY CONFIGURATIONS



STANDARD WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera & Audio

Model	LLC-1.4 Camera	WPC-2.Z Camera	AAM-TB Talkback Module
Construction	Submersible enclosure with hard-coated window	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	2.5"D x 4.0"L / .66 lbs (6.3 x 10cm / 30kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	24 Bright white LED illuminated, color camera, 480 TV Lines, 5.4° to 50° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode

Poles

Model	AP-T9
Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.
Collapsed / Extended Length	4ft. 3in. / 8ft. 7in. (1.3M / 2.6M)
Weight	6.4 lbs. (2.9kg)

Case

Model	A-CASE
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size	53" x 17" x 6" (135 x 43 x 15cm)
Weight loaded	37 lbs. (16.8kg)

System Contents:

- Detached WalkAbout III®** - 5.6" LCD Display
- LLC-1.4** - Low Light Color Camera
- AP-T14** - 14' Telescoping/Articulating Pole
- AAM-TB** - Talkback Audio Module & Headphones
- D-BAT** - D-Cell Battery Pack
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- T-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Ultra Low Light Camera

Infrared illumination, highly sensitive low-light BW camera.

Baton

2ft. fixed length pole for access in confined spaces.

Rescue Reel

Rugged reel of low signal loss cable enabling video and audio access into long vertical drops.

SYSTEM PART NUMBERS:

WS-RS-A14T¹

DISPLAYS

WS=Detached WalkAbout
WA=Standard WalkAbout

POLES

A9=9' Articulating Pole
A14=14' Articulating Pole

AUDIO

T=AAM-TB (talkback)
Blank=AAM (listen-only)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



T-CASE



AP-T14



DETACHED WALKABOUT



AAM-TB



WUH



LLC-1.4



(2) BAT-2



WBC



D-BAT

ALTERNATE DISPLAY CONFIGURATIONS



STANDARD WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera & Audio

Model	LLC-1.4 Camera	AAM-TB Talkback Module
Construction	Submersible enclosure with hard-coated window	Weatherproof enclosure; fits between pole and camera
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	1.75"D x 3.5"L / 0.34 lbs. (44mmD x 89mmL / .16kg) (Less headphones)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Omni-directional microphone; with hi-gain amplifier and compression circuit; switches between listen and talk mode

Case

Model	T-CASE
Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size	53" x 17" x 6" (135 x 43 x 15cm)
Weight loaded	40 lbs. (18.2kg)

Poles

Model	AP-T14
Construction	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.
Collapsed / Extended Length	4 ft. 1 in. / 14 ft. 1 in. (1.2M x 4.3M)
Weight	8.1 lbs. (3.7kg)

System Contents:

- Standard WalkAbout III®** - 5.6" LCD Display
- THC-36** - Thermal Camera
- RW-8** - 9' Telescoping Rigid Wand
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- N-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Low Light, Higher Magnification Camera

Infrared illumination, sensitive low-light BW camera.

Baton

2ft. fixed length pole for access in confined spaces.

SYSTEM PART NUMBERS:

WA-FEST

DISPLAYS

WA=Standard WalkAbout
 WS=Detached WalkAbout

THERMAL

None=WPC-35IR-16 Camera
 D=THC-50D + WPC-3.5IR-16 Camera

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



N-CASE



STANDARD WALKABOUT



RW-8



THC-36



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera		Pole		Cases	
Model	THC-36 Camera	Model	RW-8	Model	N-CASE
Construction	Rugged rubber booted enclosure	Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	2.5"x 2.5"x 3.7"L / 0.8 lbs. (6.4 x 6.4 x 9.4cm / .37kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	38" x 17" x 6" (135 x 43 x 15cm)
Features	320 x 240 pixels, uncooled microbolometer, 45° FOV	Articulation	None	Weight loaded	32 lbs. (15.4kg)
		Collapsed / Extended Length	3 ft. (.91M) / 7 ft. 6 in. (2.34M)		
		Weight	3.4 lbs. (1.5 kgs)		