

Under-the-Door Camera

The Zistos[®] Under-the-Door Camera is a valuable addition to any Tactical System, providing a safe and covert look into rooms that are locked or barricaded.

Features:

- Miniature CCD recessed in tongue
- IR illuminated
- Frame integration electronics provides superior image in total darkness
- Requires only a ¼" (6.4mm) door-to-floor clearance
- Integrated miniature microphone adds audio
- Audio enhancement circuitry amplifies low sounds while suppressing loud sounds
- Detachable pole with universal joint affords safe deployment and horizontal panning of room
- Direct video cable connection (without pole) for static surveillance situations
- Compatible with all Zistos systems through **VisionFlex[®]**



ORDERING INFO

- ZSV - Under-the-Door with audio
- ZSV-C - Under-the-Door with audio and cable
- ZSV-CP - Under-the-Door with audio, cable, and pole
- ZSVL - Under-the-Door without audio
- ZSVL-C - Under-the-Door without audio, with cable
- ZSVL-CP - Under-the-Door without audio, with cable and pole

SPECIFICATIONS

Sensor type	BW CCD	Sensor size	1/4"
Lux	0.005	Resolution	400 lines / 250k pixels
Illumination	6 IR LEDs	LED wavelength / Power	940 nm (invisible)
Size	0.25" / 6mm (probe height)	Weight	1.2lbs / .5kgs
Operating temp	-10° C to 50° C 14° F to 122° F	Storage temp	-20° C to 60° C -4° F to 140° F
IP rating/ submersibility	IP64	Runtime*	1hr 35min with illumination 1hr 50min without illumination
Field of view	85°	Pole/Cable	7'6" pole with universal joint 5' cable
Effective distance in good ambient light	1ft to 30ft + .3m to 9m +	Effective distance in complete darkness	1ft to 20ft + .3m to 6m +

+ Any ambient lighting significantly increases distance in complete darkness

1736 Church St, Holbrook, NY 11741 - www.zistos.com - 1-631-434-1370 - info@zistos.com

ZSV

Under-the-Door Camera

Specialty Cameras

1/1