



System Contents:

- WM-5.6-MON** - 5.6" LCD Display
- LLC-1.4** - Low Light Color Camera
- T-FNS-11** - 11' Telescoping Pole
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- S9-CASE** - Carrying Case for wand or pole
- W-CASE** - Carrying Case for all other components
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.



SYSTEM PART NUMBERS:

IA-PSW11

DISPLAYS

- IAD= Standard WalkAbout w/DVR
- ISD= Detached WalkAbout w/DVR
- IA= Standard WalkAbout
- IS= Detached WalkAbout

POLES

- 11=11' Telescoping Pole (in S9-CASE)
- 20=20' Telescoping Pole (in S20-CASE)
- W=5' Fixed length wand (in S9-CASE)

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only..

ALTERNATE DISPLAY CONFIGURATIONS





WalkAbout III Monitor		WalkAbout DVR (Alternate)
Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1 hr per GB for H.264 videos

Camera		Pole		Cases	
Model	LLC-1.4	Model	T-FNS-11	Model	W-CASE
Construction	Submersible enclosure with hard-coated window	Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Stores	WalkAbout III, camera and accessories
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	Articulation	1 ft. flexible gooseneck can be flexed into any position.	Size	21" x 16" x 8" (53 x 41 x 20cm)
		Collapsed/ Extended Length	4ft. / 10ft. 11 in. (1.22M / 3.33M)	Weight loaded	17 lbs. (7.7kg)
		Weight	4.1 lbs. (1.9kg)	Model	S-9 CASE
				Stores	T-FNS-11
				Construction	Soft padded carry case for pole
				Size	48" x 8" x 2" (122 x 20 x 5cm)
				Weight loaded	5 lbs. (2.7kg)