



System Contents:

- WM-5.6-DVR** - 5.6" LCD Display with DVR
- WPC-2.5Z** - 10:1 Color Zoom Camera
- AP-T14** - 14' Telescoping/Articulating Pole
- R-FNS** - Right Angle Adapter
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- T-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle (Power Adapter not shown)

Recommended Additions:

THC-50D Dual mode thermal camera

Locate elevated temperature components through smoke and darkness. Switch to visible light camera for better object identification

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Baton

2 Foot fixed length pole for access in confined spaces.

D-BAT

Allows use of alkaline 'D' cells when the rechargeable batteries are not charged. Good for emergency situations.

SYSTEM PART NUMBERS:

IAD - PSW - A14Z¹

DISPLAYS

IAD= Standard WalkAbout w/DVR
ISD= Detached WalkAbout w/DVR
IA= Standard WalkAbout
IS= Detached WalkAbout

POLES

A9= 9' Articulating Pole
A14= 14' Articulating Pole
14= 14' Gooseneck Pole

CAMERAS

none= LLC-1.4
Z= WPC-2.5ZCB

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



T-CASE



AP-T14



STANDARD WALKABOUT w/DVR



R-FNS



(2) BAT-2



WPC-2.5Z



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT w/DVR



STANDARD WALKABOUT



DETACHED WALKABOUT



WalkAbout III Monitor (Alternate)

WalkAbout DVR

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)	Standard: 8.8"W x 9.3"H x 4.3"D / 3.6 lbs. (22.4 x 23.6 x 10.9cm / 1.65kg) Detached Base: 6.3"W x 4.3"H x 2.9"D / 1.7 lbs. (15.9 x 10.9 x 7.3cm / .79kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing	
Display Size	5.6" (14.2cm) measured diagonally	
Resolution	640 x 480	
Operating Temperature	-4°F to 158°F (-20°C to 70°C)	-14°F to 158°F (-10°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness	
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld	
Video Format	Auto switches between NTSC (American) or PAL (European)	
Charger	12VDC from either power supply or vehicle adapter	
Batteries	NiMH, 7.2V, 2.7AH	
Discharge Time	2 hrs. with LEDs off	1.66 hrs. with camera LEDs off
Charge Time	2 hrs. when fully discharged	
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;	On/Off switch & LED; Camera illumination control & LED; Low battery LED; DVR controls
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)	
DVR	None	Up to 32GB SD card; 250 stills per GB; 1hr per GB for H.264 videos

Camera		Poles		Cases	
Model	WPC-2.5Z	Model	AP-T14	Model	T-CASE
Construction	Submersible enclosure with hard-coated window	Construction	6 Section telescoping pole, 5 internal aluminum and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	2.5"D x 4.0"L / .66 lbs (6.3 x 10cm / 30kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	53" x 17" x 6" (135 x 43 x 15cm)
Features	24 Bright white LED illuminated, color camera, 480 TV Lines, 5.4° to 50° FOV	Articulation	Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of ± 90° with detents. Twist collar allows camera angle to be locked at any position.	Weight loaded	37 lbs. (16.7kg)
		Collapsed/ Extended Length	4ft. 1in. / 14ft. 1in. (1.24M / 4.29M)		
		Weight	8.1 lbs. (3.67kg)		