



System Contents:

- Standard WalkAbout III®** - 5.6" LCD Display
- THC-36** - Thermal Camera
- RW-8** - 9' Telescoping Rigid Wand
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- N-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

Dual Mode Thermal Camera

View human activity with no illumination through smoke, tear gas and dust with thermal imaging.

Videoscope

Gain visual access into rooms or compartments through openings as small as 1/4" (6mm).

Low Light, Higher Magnification Camera

Infrared illumination, sensitive low-light BW camera.

Baton

2ft. fixed length pole for access in confined spaces.

SYSTEM PART NUMBERS:

WA-FEST

DISPLAYS

WA=Standard WalkAbout
 WS=Detached WalkAbout

THERMAL

None=WPC-35IR-16 Camera
 D=THC-50D + WPC-3.5IR-16 Camera

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



STANDARD WALKABOUT

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Camera		Pole		Cases	
Model	THC-36 Camera	Model	RW-8	Model	N-CASE
Construction	Rugged rubber booted enclosure	Construction	3 Section telescoping pole, 2 internal aluminum sections and an external fiberglass section with foam grip	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	2.5"x 2.5"x 3.7"L / 0.8 lbs. (6.4 x 6.4 x 9.4cm / .37kg)	Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	Size	38" x 17" x 6" (135 x 43 x 15cm)
Features	320 x 240 pixels, uncooled microbolometer, 45° FOV	Articulation	None	Weight loaded	32 lbs. (15.4kg)
		Collapsed / Extended Length	3 ft. (.91M) / 7 ft. 6 in. (2.34M)		
		Weight	3.4 lbs. (1.5 kgs)		