



System Contents:

- WM-5.6 WalkAbout III®** - 5.6" LCD Display
- LLC-1.4** - Two (2) Low Light Color Cameras
- WPC-3.5** - Wide Angle Color Cameras
- B-FNS** - 2' Baton
- T-FNS-14** - 14' Telescoping Pole
- RW** - 6' Rigid Wand for UVIT
- UVIT** - Under Vehicle Inspection Trolley
- BAT-2** - Two (2) NiMH Rechargeable Batteries
- WBC** - Battery Charger (Power Supply not shown)
- V-CASE** - Custom Carrying Case
- WUH** - Universal Chest Harness
- SS-WA-5.6** - Sunshade (Not shown)
- A/V Cable & Vehicle Power Adapter not shown

Recommended Additions:

- Fiberscope**
Gain visual access into compartments through openings as small as 1/4" (6mm).
- Dual Mode Thermal Camera**
Locate hidden compartments by detecting a change in temperature.

SYSTEM PART NUMBERS:

WA - VSWD14¹

DISPLAYS

WS=Detached WalkAbout
 WA=Standard WalkAbout

MODELS

D14=Includes B-FNS & (2) LLC-1.4 Cameras
 14=No B-FNS and (1) LLC-1.4 Camera
 L= No pole, no B-FNS and (1) LLC-1.4 Camera

1) Add an '-N' to specify power supply blades for the US, UK, Europe, China, Australia, otherwise supplied with US blades only.



T-FNS-14



RW



STANDARD WALKABOUT



(2) LLC-1.4



B-FNS



WPC-3.5



(2) BAT-2



WBC



WUH

ALTERNATE DISPLAY CONFIGURATIONS



DETACHED WALKABOUT



WalkAbout III Monitor

Display Size & Weight	Standard: 6.9"W x 9.4"H x 3.7"D / 3.5 lbs. (17.6 x 24 x 9.4cm / 1.58kg) Detached Base: 5.5"W x 3.7"H x 2.7"D / 1.5 lbs. (13.9 x 9.4 x 6.9cm / .66kg); LCD: 6.6"W x 7.5"H x 1.3"D / 2.5 lbs. (16.9 x 19.1 x 3.5cm / 1.13kg)
Construction	Rubber encapsulated aluminum case for shock resistance and weatherproofing
Display Size	5.6" (14.2cm) measured diagonally
Resolution	640 x 480
Operating Temperature	-4°F to 158°F (-20°C to 70°C)
LCD Controls	Brightness, contrast, color, tint, mirror, backlight & sharpness
Mounting Options	Display can be worn on vest, belt or harness; detached display can also be handheld
Video Format	Auto switches between NTSC (American) or PAL (European)
Charger	12VDC from either power supply or vehicle adapter
Batteries	NiMH, 7.2V, 2.7AH
Discharge Time/ Charge Time	2 hrs. with LEDs off / 2 hrs. when fully discharged
Base Controls & Indicators	On/Off switch & LED; Camera illumination control & LED; Low battery LED;
Connections	Camera (pole), A/V output, DC input (7.2V to 12V)

Cameras			Case	
Model	LLC-1.4 Camera	WPC-3.5	Model	V-CASE
Construction	Submersible enclosure with hard-coated window	Submersible, non-conductive enclosure with hard-coated window	Construction	Rugged, watertight, plastic carry case with foam inserts having compartments for all components.
Size & Weight	1.6"D x 2.8"L / .28 lbs (4.1 x 7.1cm / .13kg)	2.5"D x 2.6"L / .36 lbs. (6.4 x 6.6cm / .16kg)	Size	53" x 17" x 6" (135 x 43 x 15cm)
Features	9 Bright white LED illuminated, color camera, 480K pixels, .15 lux, 6.0mm lens, 47° FOV	24 Bright white LED illuminated, color camera, 380K pixels (438K/PAL), .03 lux, 3.6 mm, 92° FOV	Weight loaded	46 lbs. (20.8kg)

Poles			
Model	UVIT (Under Vehicle Inspection Trolley)	B-FNS	T-FNS-14
Construction	3 Section telescoping fiberglass detachable handle (RW-8). Rugged, aluminum trolley with 4 wheels on Trolley.	Fixed length fiberglass pole with hand grip	4 Section fiberglass telescoping
Collars	Rugged, break-proof, easy grip, twist collars for each pole section.	None	Rugged, break-proof, easy grip, twist collars for each pole section.
Articulation	Rotating handle rotates camera	1 ft. flexible gooseneck can be flexed into any position	
Collapsed/ Extended Length	Rigid Wand (RW-8): 3 ft / 7 ft 6 in. (.91M / 2.28M); Trolley (UVIT): 1ft. 9 in. (.53M)	1ft. 3in. / 2ft. 1in. (1.3M / 2.6M)	4 ft. / 13 ft. 11 in. (1.22M / 4.24M)
Weight	7.8 lbs. (combined) (3.5kg)	1.4 lbs. (2.9kg)	5.3 lbs. (2.4kg)